



STRUCTURED  
CABLING PARTNER

## Wall Mount Racks (Single Section)

**OPTIPLUS Wall Mount Single Section Racks** are best economical solution for small networking systems. Optiplus racks are fabricated by using steel sheet punched, formed, welded and powder coated with highest quality standards. The welded frame, integrated with side panel and vented top cover with fan mounting provision gives a reliable structure. Back section will have wall mounting provision.



### Overview - Features - Spec

- Complies with ANSI/EIA RS-310-D, IEC60297- 2, DIN41491:PART1, DIN41494:PART7 standards.
- Conforms to DIN41494 or equivalent standard.
- Adjustable mounting depth.
- 2 No adjustable 19" verticals with Punched 10 mm square hole and universal 12.7 mm-15.87 mm-15.87 mm. Alternating hole pattern offers greater mounting flexibility.
- Quick open side door, easy to install and maintain.
- Cable entry on both side of the rack.
- Material: SPCC quality cold rolled steel.
- Convenient and quick wall mounting.
- Turning angle of front door is over 180 degrees and lockable with keys.

### Technical Data:

Basic Frame	Steel
Construction	Welded
Top & Bottom Cover	Welded to frame with cable entry exit cutouts
Front Door	Lockable toughened glassdoor
19" Mounting Angle	Formed steel
Standard Finish	Powder coated
Standard Color	Grey & Black
Static Load	60 Kg

### Accessories:

- Fan Unit
- Cage Nuts
- Wall Bracket
- Lock

### Optional Door:

Toughened Glass Door, Metal Door, Vented Metal Door, Wave Arc Vented Metal Door.

## Ordering Information:

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>06U</b>		
OP-WM-S-6306	06U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X350X368
OP-WM-S-6406	06U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X368
OP-WM-S-6506	06U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X368

<b>09U</b>		
OP-WM-S-6409	09U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X501
OP-WM-S-6509	09U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X501

<b>12U</b>		
OP-WM-S-6412	12U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X635
OP-WM-S-6512	12U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X635
OP-WM-S-6612	12U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X600X635

<b>15U</b>		
OP-WM-S-6415	15U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X769
OP-WM-S-6515	15U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X769
OP-WM-S-6615	15U Single Section Cabinet with Glass Front Door and 2 Fans Tray	600X600X769

## Wall Mount Racks (Double Section)

**OPTIPLUS Wall Mount Double Section Racks** are very convenient for applications where security and regular maintenance is required. It is fabricated using steel sheet punched, formed, welded and powder coated with highest quality standards. Accessibility through both side of rack maximizes the flexibility for any site installation. Back section will have wall mounting provision.



### Overview - Features - Spec

- Complies with ANSI/EIA RS-310-D, IEC60297- 2, DIN41491:PART1, DIN41494:PART7 standards.
- Conforms to DIN41494 or equivalent standard.
- Adjustable mounting depth.
- 2 No adjustable 19" verticals with punched 10 mm square hole and universal 12.7 mm-15.87 mm-15.87 mm. Alternating hole pattern offers greater mounting flexibility.
- Quick open side door, easy to install and maintain.
- Cable entry on both side of the rack top and bottom.
- Material: SPCC quality cold rolled steel.
- Convenient and easy to wall mount.
- Turning angle of front door is over 180 degrees and lockable with keys.

### Technical Data:

Basic Frame	Steel
Construction	Welded
Top & Bottom Cover	Welded to frame with cable entry exit cutouts
Front Door	Lockable toughened glassdoor
19" Mounting Angle	Formed steel
Standard Finish	Powder coated
Standard Color	Grey & Black
Static Load	60 Kg

### Accessories:

- Fan Unit
- Cage Nuts
- Wall Bracket
- Lock

### Optional Door:

Toughened Glass Door, Metal Door, Vented Metal Door, Wave Arc Vented Metal Door.

## Ordering Information:

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>06U</b>		
OP-WM-D-6306	06U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X350X368
OP-WM-D-6406	06U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X368
OP-WM-D-6506	06U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X368

<b>09U</b>		
OP-WM-D-6409	09U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X501
OP-WM-D-6509	09U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X501

<b>12U</b>		
OP-WM-D-6412	12U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X635
OP-WM-D-6512	12U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X635
OP-WM-D-6612	12U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X600X635

<b>15U</b>		
OP-WM-D-6415	15U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X450X769
OP-WM-D-6515	15U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X550X769
OP-WM-D-6615	15U Double Section Cabinet with Glass Front Door and 2 Fans Tray	600X600X769

## Floor Mount Racks (Data Center Racks)

**OPTIPLUS Data Center Racks** combines the features of a high quality data center rack, it has an effective cable routing and raceway facilities as per the data center guidelines. Optiplus data center racks are manufactured out of steel sheet punched, formed, welded and powder coated with high quality standards. Static load **1200 Kg.**

### Overview - Features - Spec

- Arc vented front/rear door enable ventilation and reliable operation. Swiveling wheel and legs can be jointly installed to withstand up to 1200kg maximum static load.
- Conforms to DIN41494 or equivalent EIA/ISO/ EN/CEA standard.
- Adjustable mounting depth.
- 4 No adjustable, 19" verticals with punched 10 mm square hole and universal 12.7 mm-15.87 mm-15.87 mm. Alternating hole pattern offers greater mounting flexibility.
- Easy-to-disassembled front/rear/left/right door enable convenient operation from any side of the racks.
- Ventilation rate for door: 80-85%.
- Several lockable wiring holes on top/bottom, size can be adjusted.
- State-of-the art manufacturing methods provide the best product quality and fastest delivery in the industry.
- Large draught area: over 4500 square cm regarding 42U network cabinet.
- Powder coated finish with seven tank pretreatment process meeting ASTM standard.
- 4 fan mounting provision on top cover.



### Standard and Material:

- Comply with ANSI/EIA RS-310-D, IEC297-2, DIN41491:PART1, DIN41494:PART7, GB/T30472-92 standard, compatible with ETSI standard.
- Surface finish: Degreasing, pickling, phosphoric, powder coating.
- Material: SPCC cold rolled steel.
- Thickness: Mounting profile 2.0mm, other: 1.2-1.5mm.
- Color: RAL9005 (black), RAL7035 (grey).

### Technical Data:

Basic Frame	Steel
Construction	Welded
Top & Bottom Cover	Welded to frame with cable entry exit cutouts
Front Door	Lockable vented metal door
Back Door	Lockable double section vented door
Standing	Adjustable feet or 4 roller wheel (2 stopper)
Std. Equipment Mounting	DIN Std. 10 mm Sq. Slots
Standard Finish	Powder coated
Standard Color	Grey & Black
Rack Standard	Conforms to DIN41494 or equivalent standard
Static Load	1200 Kg
Marking	Front and back R U marking
Rack Width	19 inch

## Accessories:

- Shelf
- Fan Unit
- Cage Nut
- Castor& feet
- Lock
- Vertical Cable Manager

## Optional Door:

Metal Door, Vented Metal Door, Wave Vented Metal Door, Double Vented Metal Door, Multi-Section Door, Front Glass Door.

## Ordering Information:

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>22U</b>		
OP-DC-A-6622	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1166
OP-DC-A-6822	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1166
OP-DC-A-6022	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1166
OP-DC-A-8822	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1166
OP-DC-A-8022	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1166

<b>27U</b>		
OP-DC-A-6627	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1166
OP-DC-A-6827	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1166
OP-DC-A-6027	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1166
OP-DC-A-8827	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1166
OP-DC-A-8027	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1166

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>32U</b>		
OP-DC-A-6632	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1610
OP-DC-A-6832	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1610
OP-DC-A-6032	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1610
OP-DC-A-8832	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1610
OP-DC-A-8032	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1610

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>37U</b>		
OP-DC-A-6637	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1833
OP-DC-A-6837	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1833
OP-DC-A-6037	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1833
OP-DC-A-8837	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1833
OP-DC-A-8037	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors And Adjustable Feet	800X1000X1833

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>42U</b>		
OP-DC-A-6642	42u Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x600x2055
OP-DC-A-6842	42u Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x800x2055
OP-DC-A-6042	42u Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x1000x2055
OP-DC-A-8842	42u Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800x800x2055
OP-DC-A-8042	42u Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800x1000x2055



## Floor Mount Racks (Server Cabinet Type)

**OPTIPLUS Server Cabinet Racks** are designed for high-density server and network applications. It is ideal for extending the life of high-temp server equipment. Optiplus Server Cabinets are manufactured out of steel sheet punched, formed, welded and powder coated with high quality standards. Static load **1000Kg**.



### Overview - Features - Spec

- Arc vented front/rear door enable ventilation and reliable operation. Swiveling wheel and legs can be jointly installed to withstand up to 1000 kg maximum static load
- Conforms to DIN 41494 or equivalent EIA/ISO/ EN/CEA standard.
- Adjustable mounting depth.
- 4 No Adjustable, 19" verticals with punched 10 mm square hole and universal 12.7 mm-15.87 mm-15.87 mm. Alternating hole pattern offers greater mounting flexibility.
- Easy-to-disassembled front/rear/left/right door enable convenient operation from any side of the racks.
- Ventilation rate for door: 80-85 %.
- Several lockable wiring holes on top/bottom, size can be adjusted.
- State-of-the art manufacturing methods provide the best product quality and fastest delivery in the industry.
- Large draught area: over 4500 square cm regarding 42U network cabinet.
- Powder coated finish with seven tank pretreatment process meeting ASTM standard
- 4 fan mounting provision on top cover.

### Standard and Material:

- Comply with ANSI/EIA RS-310-D, IEC297-2, DIN41491:PART1, DIN41494:PART7, GB/T30472-92 standard, compatible with ETSI standard.
- Surface Finish: Degreasing, pickling, phosphoric, powder coating.
- Material: SPCC cold rolled steel
- Thickness: Mounting profile 2.0mm, other: 1.2-1.5mm.

### Technical Data:

Basic Frame	Steel
Construction	Welded
Top & Bottom Cover	Welded to frame with cable entry exit cutouts
Front Door	Lockable vented metal door
Back Door	Lockable double section vented door
Standing	Adjustable feet or 4 roller wheel (2 stopper)
Std. Equipment Mounting	DIN Std. 10 mm Sq. Slots
Standard Finish	Powder coated
Standard Color	Grey & Black
Rack Standard	Conforms to DIN41494 or equivalent standard
Static Load	1000 Kg
Marking	Front and back R U marking
Rack Width	19 inch

## Accessories:

- Shelf
- Fan Unit
- Cage Nut
- Castor & Feet
- Lock
- Vertical Cable Manager

## Optional Door:

Metal Door, Vented Metal Door, Wave Vented Metal Door, Double Vented Metal Door, Multi-Section Door, Front Glass Door.

## Ordering Information:

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>18U</b>		
OP-SC-A-6618	18U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray ,Fixed Shelf, Castors and Adjustable Feet	600X600X988
OP-SC-A-6818	18U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X988
OP-SC-A-6018	18U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X988
OP-SC-A-8818	18U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X988
OP-SC-A-8018	18U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X988
<b>22U</b>		
OP-SC-A-6622	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1166
OP-SC-A-6822	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1166
OP-SC-A-6022	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1166
OP-SC-A-8822	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1166
OP-SC-A-8022	22U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1166
<b>27U</b>		
OP-SC-A-6627	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1388
OP-SC-A-6827	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1388
OP-SC-A-6027	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1388
OP-SC-A-8827	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1388
OP-SC-A-8027	27U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1388

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>32U</b>		
OP-SC-A-6632	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1610
OP-SC-A-6832	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1610
OP-SC-A-6032	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1610
OP-SC-A-8832	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1610
OP-SC-A-8032	32U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1610

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>37U</b>		
OP-SC-A-6637	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X600X1833
OP-SC-A-6837	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X800X1833
OP-SC-A-6037	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600X1000X1833
OP-SC-A-8837	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X800X1833
OP-SC-A-8037	37U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800X1000X1833

MODEL	DESCRIPTION	DIMENSION (W X D X H) mm
<b>42U</b>		
OP-SC-A-6642	42U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x600x2055
OP-SC-A-6842	42U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x800x2055
OP-SC-A-6042	42U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	600x1000x2055
OP-SC-A-8842	42U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800x800x2055
OP-SC-A-8042	42U Rack with Vented Front Door and Rear Double Doors, 4 Fans Tray, Fixed Shelf, Castors and Adjustable Feet	800x1000x2055

## Power Distribution Unit

**OPTIPLUS** Power Distribution Units provide evenly distributed electrical power to servers and rack accessories. Both horizontally and vertically we can mount the PDU. It is an extremely compact solution. The body of Optiplus Power Distribution Unit is made of natural anodized aluminum.



### Design & Materials:

Shell Material and Colour	Aluminum; Black
Outlet Qty	6 way, 8 way, 10 way
Power Input Style	Left end single input style
Bracket Installation Style	Frontal installation style
Control Function	Switch

### Ordering information:

PART NUMBER	DESCRIPTION
OP-PA-0615	6 Way PDU with 1.5m
OP-PA-0613	6 Way PDU with 3m
OP-PA-0815	8 Way PDU with 1.5m
OP-PA-0813	8 Way PDU with 3m
OP-PA-1015	10 Way PDU with 1.5m
OP-PA-1013	10 Way PDU with 3m

## CABINET ACCESSORIES

### Fixed Shelf:

**OPTIPLUS Fixed Shelf** is used for 19" installation. It can be used for secure placing of equipment's inside the rack.

### Specifications

Material : 1.2mm SPCC cold rolled steel  
 Color : Black  
 Surface Finish : Powder coated  
 Load Capacity : 70KG



### Ordering information:

PART NUMBER	DESCRIPTION	SIZE(MM)
OP-FS-0619	19" fixed shelf for floor mounted cabinets	600x475
OP-FS-0819	19" fixed shelf for floor mounted cabinets	800x475
OP-FS-0919	19" fixed shelf for floor mounted cabinets	900x475

### Heavy Duty Fixed Shelf:

**OPTIPLUS Heavy Duty Shelves** are constructed in a special manner in order to accommodate particular mounting needs.

### Specifications

Material : 1.2 mm SPCC cold rolled steel  
 Color : Black  
 Surface Finish : Powder coated  
 Load Capacity : 100 KG



### Ordering information:

PART NUMBER	DESCRIPTION	SIZE(MM)
OP-HFS-0619	19" Heavy duty fixed shelf for floor mounted cabinets	600x475
OP-HFS-0819	19" Heavy duty fixed shelf for floor mounted cabinets	800x475
OP-HFS-0919	19" Heavy duty fixed shelf for floor mounted cabinets	900x475

## Sliding Shelf:

**OPTIPLUS Sliding Shelves** are useful for positioning non-rack mountable equipment in a server rack which needs frequent access.

### Specifications

Material : 1.2 mm SPCC cold rolled steel  
 Color : Black  
 Surface Finish : Powder coated  
 Load Capacity : 60KG



### Ordering information:

PART NUMBER	DESCRIPTION	SIZE(MM)
OP-SS-0619	19" Sliding shelf for floor mounted cabinets	600x475
OP-SS-0819	19" Sliding shelf for floor mounted cabinets	800x475
OP-SS-0919	19" Sliding shelf for floor mounted cabinets	900x475

## Fan Unit:

**OPTIPLUS Fan Unit** are used in network cabinets to adjust inner temperature. It maintains a safe operating temperature for servers and networking equipment's.

### Specifications

Material : SPCC cold rolled steel  
 Color : Black  
 Surface Finish : Powder coated  
 Voltage : 230V AC/ 115V AC



### Ordering information:

PART NUMBER	DESCRIPTION
OP-FU-0602	Fan Unit with 2 fans
OP-FU-0604	Fan Unit with 4 fans
OP-FU-0804	Fan Unit with 4 fans
OP-FU-0904	Fan Unit with 4 fans
OP-1U-0602	1U Fan Unit with 2 fans
OP-1U-0604	1U Fan Unit with 4 fans

## Box type Cable Management

**OPTIPLUS Box type Cable Management** is used to control and manage patch cables. Finned design, combined with channel cover.

### Specifications

Material : SPCC cold rolled steel  
 Color : Black  
 Surface Finish : Powder coated



### Ordering information:

PART NUMBER	DESCRIPTION
OP-MCB-0619	19" Cable management with metal cover

## Metal Ring Type Cable Management:

**OPTIPLUS Metal Ring Type Cable Management** can organize the cables in a professional way. It consists of steel rings for cable routing without damage from over tightened cable ties.

### Specifications

Material : SPCC cold rolled steel  
 Color : BLACK  
 Surface Finish : Powder coated



### Ordering information:

PART NUMBER	DESCRIPTION
OP-MRC-0619	19" Cable management with metal rings

## Brush Type Cable Management:

**OPTIPLUS Brush Type Cable Management** makes easier to organize cables in all types of cabinets.

### Specifications

Material : SPCC cold rolled steel  
Color : Black  
Surface Finish : Powder coated



### Ordering information:

PART NUMBER	DESCRIPTION
OP-BP-0619	19" Cable management with brush panel

## Adjustable Feet:

**OPTIPLUS Adjustable Feet** is to hold rack and adjust the height of rack. Leveling feet allow cabinet to be installed on uneven surface.

### Specifications

Material : SPCC cold rolled steel  
Color : Black  
Surface Finish : Powder coated  
Load Capacity : 270 – 330 Kg



### Ordering information:

PART NUMBER	DESCRIPTION
OP-AF-0619	Adjustable feet for Racks



## Castors:

**OPTIPLUS Castors** can be of either heavy duty or light duty. Also available in different sizes with break/without breaks.



### Ordering information:

PART NUMBER	DESCRIPTION
OP- CB-0619H	Heavy duty castors with break
OP- CB-0619L	Light duty castors with break
OPC-0619H	Heavy duty castors without break
OPC-0619L	Light duty castors without break

## Cage Nuts:

**OPTIPLUS Cage Nuts** are designed to be used in any kind of assembly including blind assemblies and are particularly common in equipment racks. No special tools or specialized fitters are required to mount these nuts.



### Specifications

Cage : Stainless steel 18/8  
 Nut : Steel Cr3 White zinc-plated

### Ordering information:

PART NUMBER	DESCRIPTION
OP-CN-0619	Cage Nuts for racks



Optiplus Networks LLC

7950 NW 53<sup>RD</sup> Street, Suite 337,  
Miami, FL.US 33166

Email: [info@optiplusnetworks.com](mailto:info@optiplusnetworks.com)

Tel: +1 7868 716663

[www.optiplusnetworks.com](http://www.optiplusnetworks.com)