



STRUCTURED
CABLING PARTNER

Category 6 U/UTP Patch Cord

OPTIPLUS Category 6 U/UTP Patch Cord ensures optimum performance from the cabling system. Optiplus factory molded patch cords are individually tested as per ANSI/TIA-568-C.2 channel standard. Patch cords are available with Cat 6 solid 23 AWG cable or Cat 6 strand cables. Optiplus patch cords are manufacturing with standard compliant RJ-45 modular plugs and it is tested for transmission frequencies to 250MHz.

Standards

- ANSI/TIA-568-C.2
- TIA/EIA 568-B.2-1
- ISO/IEC 11801
- ISO/IEC 611156-2
- EN 50288-6-2
- EN 50173-1
- IEEE /802.af, IEEE 802.3at for PoE applications



Construction:

Conductor Material	23AWG Solid Bare Copper
Insulation Material	HDPE (HIGH DENSITY POLY ETHYLENE)
Number of Conductors	8 Nos
Jacket and Boot Material	PVC/LSZH
Jacket and Boot Color	As per requirement
Cable Overall Diameter	6.0mm max.

Electrical and Mechanical Characteristics:

- Impedance - 100 Ω ± 15%
- Frequency - 1 MHz to 250 MHz
- DC Resistance - 73 Ω/100m
- Capacitance - 5.6nF/100m
- Propagation Delay Skew - 35 nsec/100m
- Dielectric Strength - 1KV/minute
- Operating Temperature - -20°C to 75°C
- Storage Temperature - 0°C to 80°C

Ordering Information:

PART NUMBER	DESCRIPTION	LENGTH
OP-C614002301/PVC	Category 6 U/UTP Patch Cord PVC 01m	1m
OP-C614002302/PVC	Category 6 U/UTP Patch Cord PVC 02m	2m
OP-C614002303/PVC	Category 6 U/UTP Patch Cord PVC 03m	3m
OP-C614002305/PVC	Category 6 U/UTP Patch Cord PVC 05m	5m
OP-C614002310/PVC	Category 6 U/UTP Patch Cord PVC 10m	10m
OP-C614002301/LSZH	Category 6 U/UTP Patch Cord LSZH 01m	1m
OP-C614002302/LSZH	Category 6 U/UTP Patch Cord LSZH 02m	2m
OP-C614002303/LSZH	Category 6 U/UTP Patch Cord LSZH 03m	3m
OP-C614002305/LSZH	Category 6 U/UTP Patch Cord LSZH 05m	5m
OP-C614002310/LSZH	Category 6 U/UTP Patch Cord LSZH 10m	10m



Optiplus Networks LLC

7950 NW 53RD Street, Suite 337,
Miami, FL.US 33166

Email: info@optiplusnetworks.com

Tel: +1 7868 716663

www.optiplusnetworks.com