

Model: OP-P2020

Feature:

- 1 / 3" CMOS progressive scan, 20x optical zoom
- HD network video output : 1920 x 1080P@25 / 30fps
- H.264 image compression format
- TCP / IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
- SD card local storage, network remote storage
- Web GUI Menu
- Support selected area amplification and PTZ function
- Provide standard SDK, easy to integrate with other digital system
- CVBS video output
- IP66 ingress protection; 4KV lightning protection, surge protection
- 100m IR night view distance



Specification:

Model	
Camera	
Image sensor	1/3" Progressive CMOS
Image pixels	1920x1080
Horizontal resolution	1000TVL
Min. Illumination	0 Lux
IR distance	100m
WB	Auto/Manual
S/N Ratio	>50dB
Day/night	Auto/Manual/Timing
Focus mode	Auto/Manual
Lens	20xZoom,f=4.7~94mm,F1.6~F3.5
PTZ	
Pan range	360 endless rotation
Pan speed	Preset Speed: 240° /S; Manual Control Speed:0.5~90° /S
Tilt range	0~90° (auto rotation)
Tilt speed	Preset Speed: 240° /S; Manual Control Speed:0.5~90°/S
SYSTEM	
PTZ control	Support
Preset	255
Patrol	8
Trace	4
Time Task	8
Scan	2

Home position display	Support
Auto Flip	Support
Alarm input	7CH(NC/NO)
Alarm output	1CH
Alarm linkage	Support
Network Function	
Compression	H.264
Frame rate	1~30FPS(25FPS)
Protocal	TCP/IP,UDP,DHCP,DDNS,NTP,RTSP,SMTP,FTP,PPPoE
Storage	SD card local storage,network remote storage
Smart alarm	Motion ,Sensor
Resolution	1920*1080,1280*720,640*480,320*240,160*120
Multi-stream	Support
PORT	
Network interface	10Base-T/100Base-TX,RJ45
Audio	Mic input*1,Mic output*1
Analog output	CVBS
OTHERS	
Control	RS485/Network
Power supply	AC24V/3000mA
Power consumption	15W(max.65W,IR on Heater on)
Working environment	Temperature:-20°C ~ 60°C; Humidity:less than 95%
Protection level	IP66, IK10
Weight	5KG
Dimensions(mm)	Φ216mm x 349mm