

Model: OP-NVR-8204PL

Feature:

- O Support 4CH 1080P@15fps or 4CH 1080P@30fps or 4CH 720P@30fps IP input
- Intuitive and user-friendly Graphic User Interface(GUI), Windows style, operation by mouse
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Multi-mode recording: manual, timer, motion, sensor
- Playback: 4CH simultaneous playback
- Search: time/calendar,events (alarm, motion)
- Express and flexible backup via USB, network or DVD-RW(Sata)
- O Pentaplex: live, record, playback, backup and remote operation
- Dual stream technology to encode recording stream and network stream respectively.
 User can adjust network stream to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- HDMI 1080P output
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting Windows phone, iPhone, Blackberry.
 Compatible with 3G
- O Complete SDK function, easy to integrate with other applications
- Edit audio and video functions like masking objects (hiding objects), choosing day and time from recorded events, adding legends, choosing audio and video quality (128K~2Mbps, frames quantity, brightness, color, etc.), cutting files (choosing especial events - audio and video)



	Model	OPTIS
SYSTEM	Compression	Monitor:D1; VGA:HD ; HDMI:HD
	CPU	1080P/720P/960H/D1/HD1/CIF/QCIF
	OS	24*1080P
VIDEO	Output	BNC*1
		VGA*1:1080P(1920*1080)
		HDMI*1:1080P(1920*1080)
IP INPUT	1080P	4CH@30fps
		4CH@15fps
	720P	4CH@30fps
	D1	4CH@30fps
AUDIO	Input	No
	Output	RCA*1
	2-way audio	RCA*1





RECORD	Resolution	1080P(1920*1080)/720P(1280*720)/D1(704*576)
	Frame rate (fps)	1~25fps/CH(PAL) 1~30fps/CH(NTSC)
	Bit Rate	2M~12Mbps
	Encode	VBR/CBR
	Quality	6 level
	Mode	Manual, Timer, Motion, Sensor
	File manage	Lock, unlock, reserving time,
PLAY	Playback	4CH
	Search	Time/Calendar search, event (motion, sensor)
	Function	Play, Pause, FF, FB;Digital zoom
ALARM	Mode	Sensor, Motion, Video Loss
	Input	4CH
	Output	1CH
	Triggering	Record, PTZ move, Relay out, e-mail, etc
NETWORK	Interface	RJ45 *1
	Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
	Others	18users online,dual stream
CELL PHONE	OS	iPhone, Blackberry, Andriod, Windows phone
	Function	Multi-channel display,server list,recording,PTZ,etc.
PORT	HDD	SATAx 2,
	RS485	RS485*1, support PTZ and Keyboard
	USB	USB2.0 x 2, one for mouse, another for USB backup device
	Remote controller	Yes
OTHERS	Power supply	DC12V
	Dimensions	430mm *300mm *55mm (W*D* H)
	Working Environment	0~50°C, 10%~90% (Humidity)